Uncoated Papers

Toner
CrystalPoint
WaterBased Ink
UVgel
UV Curable
Latex

LFM055 Red Label Zero Paper - FSC 75 g/m^2

Product Description

An FSC certified, paper, delivered at your doorstep to **support your CO2 net zero goals**. This quality paper has a high whiteness. An excellent paper when your documents must reflect the image of your work and organisation.

Physical Properties

Weight	75 g/m^2	ISO 536	Thickness	102 µm	ISO 534
Bulk	1.36 cm^3/g	ISO 534	Roughness	220 ml/min	ISO 8791-2 Bendtsen
CIE Whiteness	164.0 %	ISO 11475	Opacity	93 %	ISO 2471

All values listed are target values

Applications/ features

High quality drawings and posters
ISO 9706 standard for permanence
EMAS and ISO 14001 certified
FSC Chain-of-Custody certified
Climate Partner Certified. (www.climatepartner.com/11168-1401-101)

Available Widths (mm)

3” core	210	297	420	594	620	841	914	1067		

Refer for our current offering to www.canon-europe.com/mediaguide

Storage Conditions

Shelf life: 2 years, Temperature 21°C, Relative Humidity 50%.
Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours before printing.

Print Conditions

Best results are obtained between 20-27°C and 30–60% RH.

Environment, Health & Safety

No Material Safety Data Sheet required. Paper waste suitable for recycling.

Lamination Compatibility

Cold	Warm	Hot
yes	yes	yes

Cold: pressure sensitive
Warm: heat activated: 85°C - 95°C
Hot: heat activated: 105°C -130°C

Outdoor Use

Developed for indoor use.

Colour Profiles

Canon develops high-quality colour profiles for media / ink / printer / RIP combinations.
Check availability of profiles for your printer on www.canon-europe.com/mediaguide

Environmental Certification

FSC www.fsc.org MIX Paper | Supporting responsible forestry FSC® C008945

EU Ecolabel www.ecolabel.eu

ClimatePartner certified product
climate-id.com/W9ITWY

CO2 measure reduce contribute

ISO 9706

Processing Guidelines

Printing guidelines

Allow material to adapt to room conditions for 24 hours before printing.
It is recommended to handle the media with cotton gloves Make sure that the media comes not into contact with grease, oil, silicon, and dirt to avoid printing defects.
Insert media with care in the printers. Incorrect loading can cause skewing or creasing. Allow material to adapt to room conditions for 24 hours before printing. It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printers.
Ink/toner restrictions and printer settings have to be set for specific printers to obtain the best results. Canon colour profiles include recommended ink restrictions and printer settings for Canon supported printers.

For UVgel technology, only compatible in matte print modes.

Application guidelines

When laminating CrystalPoint® prints pressure sensitive laminates are recommended.
A laminator with soft rubber rollers is preferred.
For optimal results temperature should be set between 55-60 °C.

Standard disclaimer:
All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition 0615
© Canon Europa N.V., 2025